



MLVS2220ZP50842



外觀&形狀




INPAQ TECHNOLOGY CO., LTD.



INPAQ TECHNOLOGY CO., LTD.

Unit: mm	2220	
L	5.70±0.4	
W	5.20±0.4	
T	3.0 Max (AP)	2.8 Max (ZP)
C	1.4 Max	



注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

規格

長(公釐)	5.7
寬(公釐)	5.2
高(公釐)	2.8 Max.
尺寸代碼 英吋(公釐)	2220 (5650)
工作電壓(V)	50
工作電壓(V)	65
崩潰電壓(V)	73.8
崩潰電壓(V)	90.2
箝制電壓(A)	10
箝制電壓(V)	135
電容(KHZ)	1
電容(pF)	-
電容(pF)	8400
電容(pF)	-
突波電流(A)	4500
暫態能量(Joul)	-

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

特點

VRMS – Maximum AC operating voltage the varistor can maintain and not exceed 10µA leakage current

VDC – Maximum DC operating voltage the varistor can maintain and not exceed 10µA leakage current

VV – Voltage across the device measured at 1mA DC current. Equivalent to Vb, “Breakdown Voltage”.

Vc – Maximum peak voltage across the varistor measured at 8/20us waveform and 1A pulse current

Cp – Device capacitance measured with zero volt bias 1Vrms at 1MHz.

imax – Maximum peak current which may be applied with 8/20us waveform without device failure

Wmax – Maximum energy that may be dissipated with the 10/1000us waveform without device failure

包裝訊息

包裝尺寸(Inch)	載帶	標準包裝(KPCS)	單重(gram)	濕敏等級
13	Plastic type	2	0.42	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。