


CSME0628D-3R0N



外觀&形狀



INPAQ TECHNOLOGY CO., LTD.

| Unit:mm | | | | | | |
|---------|------|------|------|------|------|------|
| ITEM | M1 | M2 | M3 | M4 | M5 | M6 |
| DIM. | 6.00 | 6.00 | 2.80 | 4.90 | 1.55 | 2.90 |
| TOL. | ±0.3 | ±0.3 | MAX. | ±0.3 | ±0.3 | ±0.3 |




注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

規格

| | |
|-------------|-----------------|
| 長(公釐) | 6.0±0.3 |
| 寬(公釐) | 6.0±0.3 |
| 高(公釐) | 2.8 Max. |
| 尺寸代碼 英吋(公釐) | 0628 |
| 感值(uH) | 3.0±30% |
| 最大值直流阻抗(mΩ) | 23 |
| 最大飽和電流(A) | 3.6 |
| 最大溫升電流(A) | 3.4 |
| 操作溫度 | -40°C to +125°C |



注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

特點

- High saturation current realized by material properties and structure design.
- Low DC resistance to achieve high conversion efficiency and lower temperature rising.
- Low Profile: 6.0 mm × 6.0 mm × 2.8 mm.
- Magnetically shielded structure to accomplish high resolution in EMC protection.
- Halogen free, Lead Free, RoHS Compliance.
- Surface marking : None.
- The moisture sensitivity level (MSL) of products is level 1.

包裝訊息

| 包裝尺寸(Inch) | 標準包裝(KPCS) | 單重(gram) | 濕敏等級 |
|------------|------------|----------|------|
| 13 | 2 | 0.372 | 1 |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

- 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
- 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。