


## CSME0840D-220M



## 外觀&amp;形狀



| INPAQ TECHNOLOGY CO., LTD. Unit:mm |      |      |      |      |      |      |
|------------------------------------|------|------|------|------|------|------|
| ITEM                               | M1   | M2   | M3   | M4   | M5   | M6   |
| DIM.                               | 8.00 | 8.00 | 4.20 | 5.60 | 7.50 | 2.20 |
| TOL.                               | ±0.2 | ±0.2 | MAX. |      |      |      |

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

 規格

|             |                 |
|-------------|-----------------|
| 長(公釐)       | 8.0±0.2         |
| 寬(公釐)       | 8.0±0.2         |
| 高(公釐)       | 4.2 Max.        |
| 尺寸代碼 英吋(公釐) | 0840            |
| 感值(uH)      | 22±20%          |
| 最大值直流阻抗(mΩ) | 85.8            |
| 最大飽和電流(A)   | 2.8             |
| 最大溫升電流(A)   | 2.6             |
| 操作溫度        | -25°C to +125°C |

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## 特點

- ▮ High saturation current realized by material properties and structure design.
- ▮ Low DC resistance to achieve high conversion efficiency and lower temperature rising.
- ▮ Low Profile: 8.0 mm × 8.0 mm × 4.2 mm.
- ▮ Magnetically shielded structure to accomplish high resolution in EMC protection.
- ▮ Halogen free, Lead Free, RoHS Compliance.
- ▮ Surface marking : None.
- ▮ The moisture sensitivity level (MSL) of products is level 1.

## 包裝訊息

| 包裝尺寸(Inch) | 標準包裝(KPCS) | 單重(gram) | 濕敏等級 |
|------------|------------|----------|------|
| 13         | 1          | 0.99     | 1    |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。